

# Estoform OB

## High Efficient Mould Releasing Agent

### Description

**Estoform OB** is specially blended with high efficient releasing properties. It is oil based and supplied in a pale straw coloured liquid. **Estoform OB** shall be used as supplied without adding in with any water or solvent.

### Uses

It is specially design to provide quick, clean and easy stripping of moulds and formworks.

### Advantages

- Ensure stain-free concrete
- Oil based inhibits corrosion of steel formworks
- Can be used on all types of formworks
- Minimizes cleaning moulds or formworks

### Physical Properties

Specific Gravity at 25°C	0.9
Colour	Pale straw
Service Temperature	70°C max

### Application Instructions

#### Preparation of new moulds

No surface preparation is required.

#### Preparation of used moulds

All adherent materials must be removed prior to use. The moulds or formworks shall be clean before application of **Estoform OB**.

### Mixing

No mixing is required.

### Application

Use brush, sponge or conventional mould oil sprayer to apply **Estoform OB**. The correct nozzle size should be ensured, if a sprayer is used. Ponding or accumulation of excess mould oil should be avoided. It should be applied in a continuous even film.

For absorbance surfaces, it is recommended to recoat if there is a delay period for more than 48 hours.

### Cleaning

The spillages of **Estoform OB** should be absorbed into sand, earth or vermiculite and transfer to suitable container.

### Packing & Size

<b>Estoform OB</b>	210 litre drum
	20 litre pail

### Coverage

<b>Estoform OB</b>	20 to 60 m <sup>2</sup> /litre, depend on type and porosity of steel mould used
--------------------	---

### Technical Support

Denka offers a comprehensive range of high performance, high quality of repair product for both new and existing concrete surfaces. In addition, the company offers a technical support package to specifies, end-users and contractors, as well as on-site technical assistance.

### Storage

**Estoform OB** should be stored on pallets under dry conditions in original un-open drum. Under these conditions the product will have a shelf life of 12 months.

If stored in extreme heat locations the shelf life may be reduced

### Fire

**Estoform OB** is flammable. Adequate ventilation should be ensured when use. Do not use near naked fire or smoke during use.

### Precaution

**Estoform OB** should not be swallowed and avoid to be in contact with skin or eyes. Wear gloves and goggles for protection. If swallowed, seek medical attention immediately

Do not induce vomiting.

150801

## Additional Information

**Denka Construction Solutions Malaysia Sdn Bhd** offers a wide range of complementary products which includes waterstops, waterproofing products, grouts, anchors, specialized flooring products. In addition, a wide range of products formulated for repair and refurbishment of spalled concrete are available.



**Denka Construction Solutions Malaysia Sdn Bhd**  
(591858-U)

No. 18, Jalan Utas 15/7, Seksyen 15,  
40200 Shah Alam, Selangor Darul Ehsan, Malaysia  
Tel: +603 5510 8810 Fax: +603 5518 8202

[www.denka-cs.com](http://www.denka-cs.com)

## Limitation of Liability

*The information contained in this brochure provides general advice for potential customers for DENKA about the basic properties and characteristics of various DENKA products (hereafter known as "the Product Information"). DENKA makes no warranty or representation as to the entire accuracy or completeness of the Product Information in the brochure. Nothing in this brochure will be deemed to create any express or implied warranty of merchantability, fitness for a particular purpose or infringement of any intellectual property rights. Each user of the Product Information and DENKA products assumes their own responsibility to properly determine the manner and suitability of use of the Product Information and DENKA products in its own operations. The user should exercise proper care in considering the Material Safety Data Sheet, Product Information and any other technical information provided by DENKA including descriptions of the conditions of use, warnings and other cautionary instructions. DENKA reserves the right to change the Product Information from time to time at its discretion and without notice.*