

Estop Admix WP

Integral Liquid Waterproofer and Plasticiser

Description

Estop Admix WP is an integral waterproofer and plasticiser specially designed for the complete and permanent waterproofing of mass and reinforced concrete structures, cement renders, ready-mixed and precast concrete, etc.

Uses

- To improve waterproofing property of concrete and mortar
- A cost effective means of reducing concrete permeability and thereby reducing penetration

Advantages

- Improves impermeability properties
- Reduces surfaces absorption
- Allows the reduction of water cement ratio
- Improved workability and plasticity
- Minimizes cracking and plastic shrinkage
- Minimizes bleeding and segregation
- Increases compressive and tensile strength

Standard Compliance

- ASTM Type A
- BS 5075 : Part 1 : 1982
- CRD-C 163-92

Application Instructions

Estop Admix WP is required to be dispersed in water prior to addition to the concrete and Portland cement mortar mixes.

If added to transit or ready-mix truck, minimum one minute mixing is required before discharging.

Estop Admix WP is chloride free and is compatible to most type of retarding plasticizer and superplasticizer which are lignosulphonate or sulphonated naphthalene base etc. contact Estop technical department for further details.

Typical Dosage

Estop Admix WP may be dispersed to the gauging water at the rate of 1 litre per 100 kg of portland cement. For severe condition, a maximum of 1 ½ dose (1.5L) is recommended.

The use of **Estop Admix WP** allows the reduction of water cement ratio by about 10%. In doing so, a higher compressive strength can be achieved.

Test Result

The following data are compiled from our investigations and laboratory testings.

Mix Proportion	Control	Treated
OPC	1.00	1.00
Sand	3.00	3.00
W/C ratio	0.50	0.45
Admixture	Nil	1000 ml

The effect of Estop Admix WP on Permeability (ml/m²/sec) – CRD-C 163-92

Time	Control	Treated
24 hrs	0.0250	0.0220
48hrs	0.0160	0.0145
72hrs	0.0097	0.0085

Packing & Size

Estop Admix WP	20L/Pail
	200L/Drum

Technical Support

Denka offers a technical support package to specifiers, end-users and contractors, as well as on-site technical assistance.

Storage

Store in dry & covered condition. **Estop Admix WP** has a shelf life of 12 months in an unopened container.

If stored in extreme heat condition, the shelf life may be reduced.

Precaution

Suitable protective gloves and goggles should be worn. If swallowed seek medical advice immediately. Do not induce vomiting.

Estop Admix WP is water based and non-flammable.

240103

Additional Information

Denka Construction Solutions Malaysia Sdn Bhd offers a wide range of complementary products, which includes waterstops, waterproofing products, grouts, anchors, specialized flooring products. In addition, a wide range of products formulated for repair and refurbishment of spalled concrete are available.



Denka Construction Solutions Malaysia Sdn Bhd
(591858-U)

No. 18, Jalan Utas 15/7, Seksyen 15,
40200 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel: +603 5510 8810 Fax: +603 5518 8202

www.denka-cs.com

Limitation of Liability

The information contained in this brochure provides general advice for potential customers for DENKA about the basic properties and characteristics of various DENKA products (hereafter known as "the Product Information"). DENKA makes no warranty or representation as to the entire accuracy or completeness of the Product Information in the brochure. Nothing in this brochure will be deemed to create any express or implied warranty of merchantability, fitness for a particular purpose or infringement of any intellectual property rights. Each user of the Product Information and DENKA products assumes their own responsibility to properly determine the manner and suitability of use of the Product Information and DENKA products in its own operations. The user should exercise proper care in considering the Material Safety Data Sheet, Product Information and any other technical information provided by DENKA including descriptions of the conditions of use, warnings and other cautionary instructions. DENKA reserves the right to change the Product Information from time to time at its discretion and without notice.