

230501

Estop Primer E11

Epoxy Grout Primer

Description

Estop Primer E11 is a epoxy resin based primer for high strength epoxy resin grout.

Uses

Use together with high strength epoxy resin grout such as Estorex EPS for enhancing the bonding between substrate and epoxy resin grout and to prevent rust formation.

Estop Primer E11 can be applied directly onto newly cleaned steel surfaces even if they are damp.

Physical Properties

Appearance / Colour	Greyish
Density, kg/L	0.98 - 1.02

Application Instructions

Application

All metal surfaces should be cleaned to a bright finish in accordance with Swedish Standard SA 2½ or equal.

The entire contents of the hardener should be poured into the base container and mixed until homogeneous.

Apply an even coat of the **Estop Primer E11** with a brush or roller and let it become sticky before proceeding with the application of high strength epoxy resin grout such as Estorex EPS.

After this time, unused material will have stiffened and should be discarded

Packing & Size

Estop Primer E11	200ml/ Pack
-------------------------	-------------

Storage

When stored in warehouse conditions below 35°C, **Estop Primer E11** will have a shelf life of 12 months.

Technical Support

Denka offers a technical support package to specifiers, end-user and contractors, as well as on-site technical assistance.

Additional Information

Denka Construction Solutions Malaysia Sdn Bhd also offers various types of chemical repair product, which include self-adhesive, and torched-on membranes, polymer modified cementitious coatings, liquid applied coatings and rubberized bituminous emulsions etc.



Denka Construction Solutions Malaysia Sdn Bhd
(591858-U)

No. 18, Jalan Utas 15/7, Seksyen 15,
40200 Shah Alam, Selangor Darul Ehsan, Malaysia
Tel: +603 5510 8810 Fax: +603 5518 8202

www.denka-cs.com

Limitation of Liability

The information contained in this brochure provides general advice for potential customers for DENKA about the basic properties and characteristics of various DENKA products (hereafter known as "the Product Information"). DENKA makes no warranty or representation as to the entire accuracy or completeness of the Product Information in the brochure. Nothing in this brochure will be deemed to create any express or implied warranty of merchantability, fitness for a particular purpose or infringement of any intellectual property rights. Each user of the Product Information and DENKA products assumes their own responsibility to properly determine the manner and suitability of use of the Product Information and DENKA products in its own operations. The user should exercise proper care in considering the Material Safety Data Sheet, Product Information and any other technical information provided by DENKA including descriptions of the conditions of use, warnings and other cautionary instructions. DENKA reserves the right to change the Product Information from time to time at its discretion and without notice.